

**AA**  
**WATER COOLERS**  
A division of AA First Ltd

# The 1000 Series of Bottled Water Coolers

**Beautiful Design**

**Easy access to sanitise**

**Simple conversion to POU**

**Range includes Hot & Cold Table Top**

The full range consists of ...

**WCBC 1000**

Bottled, floor standing, cook & cold

**WCBH 1000**

Bottled, floor standing, hot & cold

**WCBTC 1000**

Bottled, table top, cook & cold

**WCBTH 1000**

Bottled, table top, hot & cold



*Cool...*

## From Bottled to POU in five minutes



### FEATURES AND DESIGN DETAILS CABINET

Cold-rolled 20-gauge embossed steel with baked-on acrylic enamel finish.

### DRIP TRAY

Concealed, lift-out design. High impact, durable plastic. Removable, anti-splash grid diverts drain water into tray.

### TAPS

High impact durable ABS. Fast flow. Easy to clean.

### REFRIGERATION SYSTEM

Quiet, air-cooled static-type condenser.

No fan required.

Sealed and lubricated compressor.

Protected against motor overload, Aluminium roll-bond evaporator coated with epoxy finish.

Capillary tube controls refrigerant.

Unit hermetically sealed. All joints telescoped and bazed removable insulation made of moulded expandable polystyrene. Moisture and rodent resistant.

### COOLING RESERVOIR

Type 304 stainless, polished to a satin-finish for easy maintenance. (3.8 litres capacity)

External refrigeration coil mechanically wrapped around reservoir for maximum heat transfer, expanded bead polystyrene.

### THERMOSTAT

Adjustable temperature control, conveniently located on back of cabinet for easy access.

### POWER SUPPLY

220 Volts (+10%) 50/60Hz. Provided with three pin plug, and 180cm power cord. Units for other power supply available on special order.

### DIMENSIONS (without bottle)

Floor standing: Height: 1030mm  
Width: 340mm  
Depth: 335mm

Table top: Height: 560mm  
Width: 340mm  
Depth: 335mm

### SHIPPING WEIGHT

Floor standing hot/cold: 23kg  
Table top hot/cold: 16kg

### HOT WATER TANK

High quality stainless steel. Capacity 2 litres.

Easily accessible drain. Designed to prevent total drainage for heater element protection.

Baffle bypasses water cooling reservoir, permitting room temperature water to enter directly into heating tank.

### HEATING ELEMENT

430 watts, instantaneously heating, thermostat controlled. Easily removable external heating element.

