

1100 SERIES POU Water Cooler Specification Sheet

Cabinet

Cold-rolled 20 gauge embossed steel with baked on acrylic enamel finish.

Driptray

Lift out design. High impact durable plastic. Removable anti splash grid.

Taps

Push type. Made of high impact durable ABS. Easy to remove and clean.

Refrigeration System

Quiet, air cooled static-type condenser. No fan required. Protected against motor overload. Unit hermetically sealed. R-134a refrigerant.

Cooling System

Stainless steel 3 Litre cold water tank. Thermostatically controlled from 4-12 degrees Celsius.

Heating System

Stainless Steel 2 Litre tank. 430 watt instantaneous heating. Bi-metal temperature control. Designed to prevent total drainage for heating element protection. Easily accessible hot water tank drain at the back of cooler.

Power supply

220 Volt, 50/60Hz. 3 pin plug and 180 cm power cord.

Dimensions

Floor standing: H 101.5cm x W 34cm x D 33.5cm
Benchtop: H 55cm x W 34cm x D 33.5cm

The Range

WCPC1100: Floor standing Cook & Cold

WCPH1100: Floor standing Hot & Cold

WCPTC1100: Table top Cook & Cold

WCPH1100: Table top Hot & Cold

Upgrade

Use the new upgrade conversion kit 1100P to convert a bottles 1000 cooler to a POU 1100 model.

