

3300X SERIES Bottle Water Cooler Specification Sheet

Cabinet

Cold-rolled 20 gauge embossed steel with baked on acrylic enamel finish.

Driptray

Lift out design, which can be connected to mains drainage. High impact durable plastic. Removable anti splash grid.

Taps

Push type. Made of high impact durable ABS. Easy to remove and clean.

Cup Holder

Integrated cup holder with exposed locking nuts to open up for easy refilling of cups.
(Available on floor standing models only)

Removable lower front panel

Spring loaded lower front panel. Remove drip tray and simply press down to remove entire lower front panel for easy access.

Refrigeration System

Quiet, air cooled static-type condenser. No fan required. Protected against motor overload. Unit hermetically sealed. R-134a refrigerant.

Cooling System

Stainless steel 3 Litre cold water tank. Thermostatically controlled from 4-12 degrees Celsius.

Heating System

Stainless Steel 2 Litre tank. 430 watt instantaneous heating. Bi-metal temperature control. Designed to prevent total drainage for heating element protection. Easily accessible hot water tank drain at the back of cooler.

Power supply

220 Volt, 50/60Hz. 3 pin plug and 180 cm power cord.

Dimensions

Floor standing: H 117.5cm x W 34cm x D 34cm
Benchtop: H 47cm x W 34cm x D 34cm



The Range

WCBC3300X: Floor standing Cook & Cold

WCBH3300X: Floor standing Hot & Cold

WCBTC3300X: Table top Cook & Cold

WCBTH3300X: Table top Hot & Cold

**For further information contact
AA First Limited on 01635 202 489**