

AA 4400X SERIES POU Water Cooler Specification Sheet

Cabinet

Cold-rolled 20 gauge embossed steel with baked on acrylic enamel finish.

Drip tray

Lift out design, which can be connected to mains drainage. High impact durable plastic. Removable anti splash grid.

Taps

Modern push and hold solenoid taps replace the old fashioned manual taps. The push and hold action prevents leaving the tap running by mistake whilst operating as a safety tap at the same time.

New HygieneGuard Tap Cover

The spouts of the solenoid taps are protected by the New HygieneGuard tap covers. Their silver impregnation is designed to prevent hand to tap bacterial contamination. Hand to tap contamination is the most critical area (by comparison the "waterside" is much less critical). The HygieneGuard tap cover can easily be replaced.

Cup Holder

Integrated cup holder to fit 7oz and 9oz cups
(Available on floor standing models only)

Removable lower front panel

Spring loaded lower front panel. Remove drip tray and simply press down to remove entire lower front panel for easy access.

Refrigeration System

Quiet, air cooled static-type condenser. No fan required. Protected against motor overload. Unit hermetically sealed. R-134a refrigerant.

Cooling System

Stainless steel 3 Litre cold water tank.
Thermostatically controlled from 4-12 degrees Celsius.

Heating System

Stainless Steel 2 Litre tank. 430 watt instantaneous heating. Bi-metal temperature control. Designed to prevent total drainage for heating element protection. Easily accessible hot water tank drain at the back of cooler.

Power supply

220 Volt, 50/60Hz. 3 pin plug and 180 cm power cord.

Dimensions

Floor standing: H 117.5cm x W 34cm x D 34cm
Benchtop: H 47cm x W 34cm x D 34cm



The Range

WCPC4400X: Floor standing Cook & Cold

WCPH4400X: Floor standing Hot & Cold

WCPTC4400X: Table top Cook & Cold

WCPTH4400X: Table top Hot & Cold

**For further information contact
AA First Limited on 01635 202 489**