

UC800C Under Sink Chiller with Chrome Faucet A Compact, Discreet and Stylish drinking water solution



Model	UC800C
Cold Water	1.3GAL of 50°F/HR(5L of 10°C)
	Based ARI Standard from water inlet temperature of 26.7 C and ambient temperature of 32.2 C
Room Temp. Water	N/A
Dimensions	16.1"W(410mm)X8.3"D(210mm)X14.4"H(290mm)
Weight	27.6lbs(12.5kg)
Shipping Dimensions	18.3"W(465mm)X9.0"D(230mm)X13.0"H(330mm)
Shipping Weight	30.9lbs(14kg)
Inlet/Outlet Pipe Diameter	1/4"(External Diameter)X0.170"(Internal Diameter)
Optimum Material	LLDPE (Line Low Density Poly Ethylene)
Faucet as standard	Attractive chrome faucet with 1/4" pipe attached
Allowed Pressure	700kPa
Cabinet	High quality material with strong corrosion resistance.
Cold Water Tank	Hygienic stainless steel. External refrigerant evaporator which is mechanically wrapped around tank.
Cold Water Thermostat	Temperature is controlled to 35.6°F~53.6°F(2°C~12°C) by adjustable thermostat, easily accessible at the back of cabinet.
Refrigeration unit	Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. Refrigerant is controlled by accurately calibrated capillary tube. Highly efficient cooling system.
Refrigerant type	R134a
Electrical	220V ~ 240V (±10%) 50/60Hz, 100V ~ 127V (±10%) 50/60Hz provided with power cord.
Quality	Our models covered by these specifications are manufactured to comply with the standards of overseas quality system. CE approved
Warranty	One year on the sealed refrigeration system and most component parts.